

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

F-7187

Ser. No. 09/982,563

**IN THE CLAIMS:**

Please replace the claims with the claims provided in the listing below wherein status, amendments, additions and cancellations are indicated.

1. (Canceled)
2. (Canceled)
3. (Canceled)
4. (Canceled)
5. (Canceled)
6. (Canceled)
7. (Canceled)
8. (Canceled)

9. (Currently amended) The convertible of claim 8 18, wherein the multiple joint (114; 114.1) is a quadruple joint, two joint points (116, 117; 116.1, 117.1) being assigned to the lid part (104) and two further joint points (118, 119; 118.1, 119.1) being assigned to the auxiliary frame (111; 111.1).

10. (Canceled)
11. (Canceled)

F-7187

Ser. No. 09/982,563

12. (Canceled)
13. (Canceled)
14. (Canceled)
15. (Canceled)
16. (Canceled)
17. (Canceled)

18. (Newly added) A convertible (101) with a roof (102), which can be stowed in the rear region (103) of the vehicle beneath a lid part (104), it being possible to open and close the lid part (104), on the one hand, for unblocking an opening (107) for the passage of the roof (102), adjacent to the front end region (115) of the lid part (104) and, on the other, for unblocking an opening (108) for luggage, adjacent to the rear end region (109) of the lid part (104), an auxiliary frame (111; 111.1) being disposed beneath the lid part (104) and connected in the, in the driving direction (F), pre-disposed area over a multiple joint (114; 114.1) with the lid part (104) and mounted moveably with respect to the vehicle body in its rear region (112; 112.1), wherein the multiple joint (114; 114.1), during the unblocking of the opening (107) for the passage of the roof (102), is held in an opened position, which increases the distance between the lid part (104) and the auxiliary frame (111; 111.1) in comparison to the distance in the closed position,

F-7187

Ser. No. 09/982,563

wherein at least one elongated hole, functioning as a sliding block guide (123; 124; 123.1) is constructed for shifting the joint point or points (118, 119, 118.1, 119.1) assigned to the auxiliary frame (111, 111.1).

19. (Newly added) A convertible (101) with a roof (102), which can be stowed in the rear region (103) of the vehicle beneath a lid part (104), it being possible to open and close the lid part (104), on the one hand, for unblocking an opening (107) for the passage of the roof (102), adjacent to the front end region (115) of the lid part (104) and, on the other, for unblocking an opening (108) for luggage, adjacent to the rear end region (109) of the lid part (104), an auxiliary frame (111; 111.1) being disposed beneath the lid part (104) and connected in the, in the driving direction (F), pre-disposed area over a multiple joint (114; 114.1) with the lid part (104) and mounted moveably with respect to the vehicle body in its rear region (112; 112.1), wherein the multiple joint (114; 114.1), during the unblocking of the opening (107) for the passage of the roof (102), is held in an opened position, which increases the distance between the lid part (104) and the auxiliary frame (111; 111.1) in comparison to the distance in the closed position, wherein two joint points (118, 119) in the auxiliary frame (111) are held in two elongated holes (123; 124), which extend essentially linearly and, in the closed position, in the driving direction.

F-7187

Ser. No. 09/982,563

20. (Newly added) The convertible of claim 19, wherein the multiple joint (114; 114.1) is a quadruple joint, two joint points (116, 117; 116.1, 117.1) being assigned to the lid part (104) and two further joint points (118, 119; 118.1, 119.1) being assigned to the auxiliary frame (111; 111.1).

21. (Newly added) A convertible (101) with a roof (102), which can be stowed in the rear region (103) of the vehicle beneath a lid part (104), it being possible to open and close the lid part (104), on the one hand, for unblocking an opening (107) for the passage of the roof (102), adjacent to the front end region (115) of the lid part (104) and, on the other, for unblocking an opening (108) for luggage, adjacent to the rear end region (109) of the lid part (104), an auxiliary frame (111; 111.1) being disposed beneath the lid part (104) and connected in the, in the driving direction (F), pre-disposed area over a multiple joint (114; 114.1) with the lid part (104) and mounted moveably with respect to the vehicle body in its rear region (112; 112.1), wherein the multiple joint (114; 114.1), during the unblocking of the opening (107) for the passage of the roof (102), is held in an opened position, which increases the distance between the lid part (104) and the auxiliary frame (111; 111.1) in comparison to the distance in the closed position, wherein two joint points (118, 119) in the auxiliary frame (111) are held in two elongated holes (123; 124), which extend essentially linearly and, in the closed

F-7187

Ser. No. 09/982,563

position, in the driving direction, and wherein, in the closed position of the lid part (104), the joint points (118, 119) are held in elongated holes (123; 124) in an extreme front position and, during the opening process of the lid part (104), for unblocking the opening (107) for the passage of the roof, initially can be shifted in a rearward direction and, as the opening process is continued, can be shifted once again in the direction of the extreme front region.

22. (Newly added) The convertible of claim 22, wherein the multiple joint (114; 114.1) is a quadruple joint, two joint points (116, 117; 116.1, 117.1) being assigned to the lid part (104) and two further joint points (118, 119; 118.1, 119.1) being assigned to the auxiliary frame (111; 111.1).

23. (Newly added) A convertible (101) with a roof (102), which can be stowed in the rear region (103) of the vehicle beneath a lid part (104), it being possible to open and close the lid part (104), on the one hand, for unblocking an opening (107) for the passage of the roof (102), adjacent to the front end region (115) of the lid part (104) and, on the other, for unblocking an opening (108) for luggage, adjacent to the rear end region (109) of the lid part (104), an auxiliary frame (111; 111.1) being disposed beneath the lid part (104) and connected in the, in the driving direction (F), pre-disposed area over a multiple joint (114; 114.1)

F-7187

Ser. No. 09/982,563

with the lid part (104) and mounted moveably with respect to the vehicle body in its rear region (112; 112.1), wherein the multiple joint (114; 114.1), during the unblocking of the opening (107) for the passage of the roof (102), is held in an opened position, which increases the distance between the lid part (104) and the auxiliary frame (111; 111.1) in comparison to the distance in the closed position, wherein the joint (114.1) is a quadruple joint and two of the joint points (118.1; 119.1) are assigned to the lid part (104) and two further ones to the auxiliary frame (111.1), the joint points (118.1; 119.1), assigned to the auxiliary frame (111.1), being moveable in a common sliding-block guide (123.1).

24. (Newly added) The convertible of claim 23, wherein the multiple joint (114; 114.1) is a quadruple joint, two joint points (116, 117; 116.1, 117.1) being assigned to the lid part (104) and two further joint points (118, 119; 118.1, 119.1) being assigned to the auxiliary frame (111; 111.1).

25. (Newly added) A convertible (101) with a roof (102), which can be stowed in the rear region (103) of the vehicle beneath a lid part (104), it being possible to open and close the lid part (104), on the one hand, for unblocking an opening (107) for the passage of the roof (102), adjacent to the front end region (115) of the lid part (104) and, on the other, for unblocking an opening (108) for

F-7187

Ser. No. 09/982,563

luggage, adjacent to the rear end region (109) of the lid part (104), an auxiliary frame (111; 111.1) being disposed beneath the lid part (104) and connected in the, in the driving direction (F), pre-disposed area over a multiple joint (114; 114.1) with the lid part (104) and mounted moveably with respect to the vehicle body in its rear region (112; 112.1), wherein the multiple joint (114; 114.1), during the unblocking of the opening (107) for the passage of the roof (102), is held in an opened position, which increases the distance between the lid part (104) and the auxiliary frame (111; 111.1) in comparison to the distance in the closed position, wherein the joint (114.1) is a quadruple joint and two of the joint points (118.1; 119.1) are assigned to the lid part (104) and two further ones to the auxiliary frame (111.1), the joint points (118.1; 119.1), assigned to the auxiliary frame (111.1), being moveable in a common sliding-block guide (123.1), and wherein the sliding-block guide (123.1) is curved upward.

26. (Newly added) The convertible of claim 25, wherein the multiple joint (114; 114.1) is a quadruple joint, two joint points (116, 117; 116.1, 117.1) being assigned to the lid part (104) and two further joint points (118, 119; 118.1, 119.1) being assigned to the auxiliary frame (111; 111.1).